



SECURE YOUR SUCCESS!



# XWing



## Bidirectional Locking Security Access Gate

Lower your cost of ownership with Aeroturn XWing, our 5-year, Zero Maintenance access gate factory tested to 10 million+ cycles, offering high-performance protection in a compact package.

### FEATURES & BENEFITS

- **Superior No-Wear Geometric Locking (enter/exit)** provides locking strength that exceeds structural limit of tempered glass panel
- **Secure single pedestrian** access gate with anti-tailgating optical detection
- **Designed for virtually any situation**, unidirectional at 50 passages/minute or bidirectional by program, glass heights up to 60" (1,524 mm)
- **Low energy consumption**, 24 W (operating), 10 W (idle)
- **Small footprint, quiet operation**, can be installed in hallways without disturbing occupants
- **Durable and attractive 20-year design** includes extreme environment detectors
- **Wheelchair accessible** with lane safety

### Where XWing Turnstiles are Used



GOVERNMENT FACILITIES | BANKS | CORPORATE HEADQUARTERS | LAW ENFORCEMENT | UNIVERSITIES | UTILITIES

# XWing Turnstile Product Features

## Security

- Integrates with card and bar code readers, fingerprint and facial recognition, and elevator module
- Integrates with existing building management systems
- Tailgating alarm
- Intrusion alarm
- Optional intuitively designed Aeroturn Desk Control for remote operation

## Finishes

- Cabinet (standard): 304 SST #4 brushed parallel to ground, optional paint with color choice
- Top (standard): Solid Surface by Corian® or HI-MAC®; color choice to match décor
- Moving panel parts (standard): Aeroturn Champagne, optional paint to match cabinet
- Glass: 8 mm clear tempered safety glass
- Customizable decals: Customer seals/logos, ADA and entrance/exit placards

## Factory Installation

- Aeroturn installed anchorage and low voltage wiring and commissioning
- Optional AeroDuct floor trough wire management
- Optional platform system that requires no anchors
- Optional cable covers matched to cabinet

## Safety and Emergency

- Key operated power on/off switch
- Key operated emergency release (panels lock open)
- Optional "No Prior Knowledge" emergency egress panels
- Optional battery backup to operate 2,000 cycles without site power

## Electrical

- Relay-buffered PLC inputs
- 24 V, 4 A max inrush current
- On-board power boost for motor longevity
- Power 4 lanes with single 120 V, 20 A breaker

## Warranty / Life Expectancy


- 5-year warranty on mechanical components
- 1-year warranty on electrical components
- 20-year design
- Factory tested to 10 million+ cycles
- Optional PMs for deep internal cleaning and upgrades

## Normal Operation

- Unidirectional or bidirectional
- Top mounted LED direction indicators
- Lane safety in either direction
- Card access in either direction
- Auto-exit capable
- Site-programmable security profile

## Accessories

- Matching machine-mounted fixed-panel barrier to secure adjacent spaces
- Matching floor standing glass walls
- LED accents tunable to color range



**Schedule a Demo Today!**